

WEICONLOCK® AN 305-72 Pipe and Thread Sealing



high viscosity
medium strength
disassembly with normal tools

Pipe and flange sealing with PTFE, immediate sealing effect, DVGW-approval



Technical Data

| | |
|--|--------------------------|
| Colour | white |
| For threaded joints up to | M 80 R 3" |
| Viscosity at +25°C (+77°F) according to Brookfield | 17.000 - 50.000 ht mPa·s |
| Max. gap bridging | 0,4 mm |
| Breakaway strength (Thread) | 7 - 10 Nm |
| Prevailing strength | 2 - 4 Nm |
| Shear strength Nmm ² (DIN 54452) | 4 - 6 N/mm ² |
| Handling strength at room temperature | 20 - 40 min. |
| Final strength (100%) after | 5 - 10 h |
| Temperature resistance | -60 to +150 °C |
| ISSA-Code | 75.628.34/35 |
| IMPA-Code | 81 52 10/11 |

*Strength values based on M 10 screws, 8.8 grade, thickness of nut 0,8.d Static shear strength based on cylindrical parts of abt. Ø 13 mm, tolerance (D-d) = 0,05 mm, l/d = 0,88

Surface pre-treatment

In general, WEICONLOCK does not require special pretreatment as slightly oily surfaces (e.g. on as received parts) will be tolerated. However, best results will be achieved on cleaned, degreased parts (use WEICON Surface Cleaner). If required, the parts should be slightly roughened.

Processing

WEICONLOCK is ready for use and should be applied evenly direct from the bottle/tube with the dispensing tip (avoid direct contact of dispensing tip with metal). Apply WEICONLOCK in circular motions on the thread. Screw pipe threads together and tighten until desired orientation. When using as flange sealing apply a continuous bead on one side. Join and tighten parts quickly. Do not pour back into the bottle any WEICONLOCK fluid which had contact with metal; even smallest metal particles will cause the content of the bottle to cure. In series construction, the use of manual or automatic applicators is recommended.

Storage

WEICONLOCK can be stored in the unopened original container for at least 24 months at room temperature. Keep away from heat sources and direct sunlight. The air in the bottle/tube keeps WEICONLOCK liquid.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

| | |
|----------|--|
| 30572150 | WEICONLOCK® AN 305-72 Pipe and Thread Sealing 50 ml |
| 30572200 | WEICONLOCK® AN 305-72 Pipe and Thread Sealing 200 ml |
| 30572300 | WEICONLOCK® AN 305-72 Pipe and Thread Sealing 300 ml |

Accessories:

| | |
|----------|--------------------------------------|
| 11202400 | Sealant and Adhesive Remover, 400 ml |
| 11207400 | Surface Cleaner, 400 ml |
| 11850200 | Hand Protective Foam, 200 ml |
| 30700200 | Activator F, 200 ml |
| 30955172 | Dosing Tips, Size 1 |
| 30955179 | Dosing Tips, extra thin |

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG
 (Headquarters)
 Germany
 phone +49 (0) 251 9322 0
 info@weicon.de

WEICON Middle East L.L.C.
 United Arab Emirates
 phone +971 4 880 25 05
 info@weicon.ae

WEICON Inc.
 Canada
 phone +1 877 620 8889
 info@weicon.ca
 www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.
 Turkey
 phone +90 (0) 212 465 33 65
 info@weicon.com.tr
 www.weicon.com.tr

WEICON Romania SRL
 Romania
 phone +40 (0) 3 65 730 763
 office@weicon.com

WEICON SA (Pty) Ltd
 South Africa
 phone +27 (0) 21 709 0088
 info@weicon.co.za

WEICON South East Asia Pte Ltd
 Singapore
 phone (+65) 6710 7671
 info@weicon.com.sg

WEICON Czech Republic s.r.o.
 Czech Republic
 phone +42 (0) 417 533 013
 info@weiconcz.cz

WEICON Ibérica S.L.
 Spain
 phone +34 (0) 914 7997 34
 info@weicon.es